

OC1500

NATURAL CLEANER

The OC1500 Natural Cleaner is the global leader in its performance class. It is a rugged and fully mobile ozone generator designed for use by health, safety and housekeeping professionals. It can be used to sanitise rooms through the rapid and complete elimination of odours from organic compounds, such as smoke, mould, mildew, foodstuffs and sewage.

The OC1500 Natural Cleaner utilises unique patented double dielectric discharge technology to achieve an industry leading ozone output of 15,000 mg/h under ambient air conditions. This high level of ozone is particularly effective in treating bedrooms and communal spaces in hotels, care homes and office environments where traditional methods of air restoration are not effective.



UNIQUE SAFE DEACTIVATION CYCLE

The OC1500 features both an activation cycle and a fully automated deactivation cycle. This deactivation cycle rapidly clears an area of ozone, minimising the time spent performing air treatment. The OC1500 complies with **CE** UL, FCC and CSA standards.

TYPICAL APPLICATIONS

Typical applications of the OC1500 include use by hotel and restaurant personnel to remove odours from rooms contaminated by tobacco smoke or other material, as well as to eliminate odours found in function rooms, garbage storage areas and after redecoration.

Care home professionals use the OC1500 to maintain fresh smelling environments for residents and visitors.

CAUTION

The OC1500 must only be used in unoccupied spaces and in accordance with the operations manual.

ELECTRICAL SPECIFICATIONS

Input voltage: 220v, 50Hz / 120v, 60Hz

Input power: 350w

Air flow rate: 450+ CFM

PERFORMANCE SPECIFICATION

Ozone outputs: True 15,000mg/hour with ambient air input

MECHANICAL SPECIFICATIONS

Enclosure: aluminum/steel construction

Dimensions: 400 x 440 x 880 mm

Weight: 26kg

ENVIRONMENTAL LIMITS

Ambient temperature: 25 - 130 °F

Relative humidity up to 95% (non-condensing)

WARRANTY

2 Years

SAFETY FEATURES

Key switch operated to prevent unauthorised use

Re-settable manual circuit breaker

High intensity flashing light indicator

Cycle start/stop alarm

Differential air pressure regulator with auto shutdown

OTHER FEATURES

- Fully automatic activation and deactivation cycles
- Cycle time 15 minutes to 48 hours
- Control: digital keypad with large backlit display providing clear and easy to understand operator prompts
- Free parameter settings of room size and treatment time
- Large wheels for easy rolling, leaves no tracks
- 101.6mm (4") ozone output duct for optional routing to remote areas

APPLICATION PROCESS

The OC1500 ozone application process requires first removing people, pets and plants from an enclosed area. OC1500 operation is then achieved by using a built-in digital keypad to select room size and treatment time, from 15 minutes up to 48 hours.

When the OC1500 is turned on, a flashing yellow light gives the operator a one minute warning to leave the room before ozone generation begins. When ozone generation starts, the buzzer sounds 10 blasts. When treatment has been completed including the ozone deactivation cycle, the OC1500 buzzer sounds again and the flashing light goes off. The deactivation cycle has removed the residual ozone and the area may immediately be re-occupied.



For more information contact:

Ozone Clean Limited, 170 Fortis Green, London N10 3PA

Tel: +44 (0)20 8883 2756 email: sales@O3clean.co.uk

ozone clean
LIMITED